

Quotation for NRZ pluggable optical module



Overview

The modules met the same QSFP28 LR4 optical specification, supported the same 10km single-mode fiber reach, and were coded for the same switch platform. The same 400 modules would have cost \$112,000. The Arista Compatible 100GBASE-SR1.2 BiDi QSFP28 transceiver is a pluggable optical module with a duplex LC connector, designed for short-reach data communication and interconnect applications over Multi-Mode Fiber (MMF). The product can convert 8 channels of 25Gbps (NRZ) electrical input data to 4 channels. HIGH PERFORMANCE UNDER EXTREME CONDITIONS, the Amphenol AOP 28Gbps extended temperature "Quad Embedded Pluggable Transceiver" is designed for highly challenging applications where both reliability and performance are critical. Electrical: 12x 10G NRZ channels. □ Hot-pluggable CFP form factor □ Supports 39.6 Gb/s data rates □ Power dissipation < 8W (class 1) □ RoHS-6 compliant (lead-free) □ Commercial temperature range 0°C to 70°C □ Single 3.

Article Content

QSFP-DD Connector System

QSFP-DD Interconnect System's 8-lane electrical interface transmits 28G NRZ, 56G PAM-4 and 112G PAM-4, up to 200, 400 or 800 Gbps aggregate. Backwards

200G QSFP-DD ER4 EML LWDM4 40km Optical Transceiver

GIGALIGHT 200G QSFP-DD ER4 optical transceiver module is used for long-distance transmission in the field of data communication or telecommunications, and is in line with the 200G Ethernet

Arista Announces XPO High Density Liquid Cooled Pluggable Optics

"The XPO module is a breakthrough for AI data centers delivering 4X the front panel density compared to OSFP, while preserving the configurability and serviceability of a pluggable

OFC 2024 NEC Optical Modules

Optical interface Wavelength Electrical interface SFP28, Duplex 9.95-11.3Gb/s 10Gbaud, NRZ C-band, 50 channel, 100GHz grid 10GAUI, NRZ Reach 80km Power consumption 2.5W (E-Temp) Operating

FTLQ1381N7NL 40G NRZ VSR Multi-Rate CFP Optical Transceiver

This 40G NRZ CFP was designed to support very short reach (VSR) optical networking connections characterized by single mode fiber link lengths from 2m to 2 km. The FTL1381 was developed to

QSFP28 Price Guide 2026: 100G Transceiver Costs & TCO

Sandra's procurement team had a \$200,000 annual budget for optical transceivers. Her first purchase order went to the usual OEM vendor: 400 QSFP28 LR4 modules at a discounted

Introduction to 800G Optical Module

Modulation Advancement: 800G optical modules use PAM4 modulation, which supports higher data rates and improves network performance compared to traditional NRZ modulation.

Pluggable Optical Module Market Research Report 2034

The pluggable optical module market was valued at \$9.8 billion in 2025 and is projected to reach \$26.4 billion by 2034, growing at a CAGR of 11.6%.

200GBASE-2SR4 QSFP-DD PAM4 850nm 100m MMF Module for

The modulation of QDD-200G-SR8 optical module is 8X25G NRZ for both electrical side and optical side.

QEPT 4-TRX 100G NRZ

QEPT 4-TRX 100G NRZ 100 Gb/s High-Speed Optical Pluggable Module HIGH PERFORMANCE UNDER EXTREME CONDITIONS, the Amphenol AOP 28Gbps extended temperature " Quad

Arista Compatible 100GBASE-SR1.2 QSFP28 BiDi 4 x

The Arista Compatible 100GBASE-SR1.2 BiDi QSFP28 transceiver is a pluggable 120G CXP Pluggable Optical Transceiver Supporting

Contact for Quotation:Kindly email your requirements to sales@szvan for a customized quotation and optimal solution.Attn:Jessica Lee

Coherent To Demonstrate 200G Per Lane For 800G

Coherent Corp. (Nasdaq: COHR), today announced it will demonstrate an optical transceiver module operating at 200 Gbps per optical lane.

FinancialContent

This specification is a significant milestone for both the LPO MSA and networking industry. The 100G-DR-LPO specification has been validated by extensive member interoperability

Arista Compatible 100GBASE-SR1.2 QSFP28 BiDi 4 x 25G NRZ

The Arista Compatible 100GBASE-SR1.2 BiDi QSFP28 transceiver is a pluggable optical module with a duplex LC connector, designed for short-reach data communication and interconnect applications

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://e-motional.eu>

Email: info@e-motional.eu

Phone: +49-30-657-8924

Address: Friedrichstraße 101, 10117 Berlin, Germany

This document is for informational purposes only. Specifications subject to change without notice.

